PALLET TRUCK

PEDESTRIAN TYPED





TOUGH WORLD. TOUGH EQUIPMENT.

LIUGONG

Guangxi LiuGong Machinery Co.,Ltd. No. 1 Liutai Road, Liuzhou, Guangxi. 545007

PR China

T: +86 0772 3886124

E: overseas@liugong.com

HQ: www.liugong.com

MH: www.lgforklift.cn







LIUGONG 082019-ENG

The LiuGong series of logos herein, including but not limited to word marks, device marks, letter of alphabet marks and combination marks, as the registered trademarks of Guangxi LiuGong Group Co., Ltd. are used by Guangxi LiuGong Machinery Co., Ltd. with legal permission, and shall not be used without permission. Specifications and designs are subject to change without notice. Illustrations and pictures may include optional equipment and may not include all standard equipment. Equipment and options varies by regional availability.



Electric Pallet Truck

Main Features



GERMANY AC DRIVE TECHNOLOGY

- The powerful German Schabmueller maintenance free AC Drive motor in combination with the Greman Kordel gearbox, Intorqe brake and Wicke drive wheel give best performance, efficiency and reliability to reduce the running cost.
- The AC Drive can gives always the right response when gentle or fast acceleration whatever you desired.



LONG TILLER DESIGN FOR ERGONOMICS AND SAFETY

- In particular through the long tiller design the operator can always keep a safe distance to the truck during proceeding the work very ergonomically.
- The design ensures lower operational forces than trucks with a short tiller.
- The tillers operating height is naturally positioned to ergonomic, operator friendly controlling positions.



MAINTENANCE FRIENDLY

 The trucks design and the used components are tailored to make service and maintenance easy. All components are easy to reach when removing the main cover only with 2 screws, drive-and castor wheel are east to exchange without craning the truck.



S.

LONG LASTING BATTERY

- With the long lasting battery capacities for every model.
- With sideways battery exchange for long operations and multi-shifts.

SPECIFICATION

	Model	1		CLG2016L-WA		CLG2020L-WA		CLG2025L-WA	
Feature	Poer Type	2		Electric		Electric		Electric	
	Driving Type	3		Walking		Walking		Walking	
	Capacity	4	kg	1600		2000		2500	
Dimension	Overall Length	5	mm	1670		1735		1950	
	Overall Wide	6	mm	690		690		690	
	Overall Height	7	mm	1335		1335		1335	
	Min. Height of Fork	8	mm	85		85		85	
	Max. Height of Fork	9	mm	205		205		205	
	Fork	10	mm			1150×1	173×60		
	Fork Spread	11	mm	540	685	540	685	540	685
	Wheel Base	12	mm	1261		1327		1541	
	Turning Radius	13	mm	1440		1490		1750	
Performance	Driving Speed (load / unload)	14	km/h	5.7 / 6.0		5.7 / 6.0		5.5 / 6.0	
	Lifting Speed (load / unload)	15	mm/s	25 / 35		22 / 30		35 / 45	
	Lowering Speed (load / unload)	16	mm/s	35 / 30		35 / 35		40 / 40	
Motor	Driving Motor Power	17	kw	1.3		1.3		1.7	
	Lifting Motor Power	18	kw	0.8		0.8		2.2	
	Battery Capacity / Voltage	19	Ah/v	160 / 24		210 / 24		350 / 24	
Wheel Dimension	Front Wheel	20	mm			Ф84×84			
	Balance Wheel	21	mm			Ф100×40			
	Driving Wheel	22	mm			Ф230×70			
Weight	Service Weight	23	kg	445		535		720	
We	Battery	24	kg	150		215		285	

